

Platinum HD TVI 8CH DVR LTD8508T-ST




Key Features:

- Support HD-TVI / IP / Analog / AHD cameras
- CVBS output improves compatibility at the most possibility

Rear Panel:

- | | | |
|------------------|------------------|------------------|
| 1. Video In | 6. Audio Out | 11. Power Switch |
| 2.USB Interface | 7. LAN | 12. Alarm in/out |
| 3.VIDEO OUT | 8. Audio In | 13. GND |
| 4. HDMI | 9. RS-485 Serial | |
| 5. VGA Interface | 10. DC 12V | |



Platinum HD TVI 8CH DVR

LTD8508T-ST

VIDEO/ AUDIO INPUT

Video compression	H.264 Zip+ / H.264
Video input	8ch BNC (1.0 Vp-p, 75 Ω), PAL / NTSC self-adaptive
IP input	up to 2ch(Support ONVIF, up to 4MP resolution)
Audio compression	G.711u
Audio input	4-ch, RCA (2.0 Vp-p, 1 kΩ)
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ)

VIDEO/ AUDIO OUTPUT

HDMI/ VGA output	VGA: 1 -ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60 Hz HDMI: 1 -ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60 Hz
Encoding resolution	3MP@15fps/1080p@30fps/720p@30fps
CVBS output	1-ch, BNC (1.0 Vp-p, 1 kΩ)
Frame rate	Main stream: 30fps(N)/25fps(P) Sub-stream:WD1/4CIF@12fps,CIF/QVGA/QCIF@real time frame rate
Video bit rate	32 Kbps-10Mbps
Audio output	1-ch, RCA (Linear, 1 kΩ)
Audio bit rate	64 Kbps
Dual-stream	Support
Stream type	Video, Video & Audio
Synchronous playback	8ch

NETWORK

Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, PT Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF

HARD DISK

SATA	2 SATA
Capacity	Up to 8TB capacity for each disk

EXTERNAL INTERFACE

Network interface	1:10M / 100M / 1000M self-adaptive Ethernet interface
Serial interface	RS-485
USB port	2 × USB2.0
Alarm in/ out	8/4

GENERAL

Power supply	DC12V
Consumption	≤ 20W
Working temperature	-10 ° C ~ +55 ° C(14° F - 131° F)
Working humidity	10% ~ 90%
Chassis	1U chassis
Dimensions (WxDxH)	380 × 320 × 45 mm (15.0 × 12.6 × 1.8 inch)
Weight	≤ 2Kg (4.4lb)